

Type		ASC 1308	ASC 1312	ASC 1316	ASC 1324	ASC 1332
Order No.		361011	361012	361013	361014	361015
EAN code		40 26187 280109	40 26187 280116	40 26187 280123	40 26187 280130	40 26187 280147
Inputs						
Satellite / IF				12		
Terrestrial				1		
Outputs						
Loop-through		13	13	13	13	13
Receiver		8	12	16	24	32
Further data						
Frequency range	SAT / IF	[MHz]		950 - 2150		
	Terrestrial			47 - 870		
Terrestrial amplifier		[dB]		23 - 25		
Gain	SAT / IF	[dB]	+3±1	+2±1	+2±1	+1±1
	Terrestrial		-1±1	-2±1	-3±1	-6±1
Equalizer	SAT	[dB]		+4±1		
Cascade loss	SAT / IF	[dB]	-2±1	-2±1	-3±1	-4±1
	Terrestrial		-5±1	-5±1	-5±1	-5±1
Max. signal input	SAT / IF	[dBμV]		98		
	Terrestrial			81		
Max. signal output	SAT / IF	[dBμV]		102		
	Terrestrial			85		
Return loss inputs / outputs		[dB]		10 / 14		
Isolation	SAT / SAT	[dB]		>33		
	SAT / Terr.			>37		
Current consumption receiver output		[mA]		41		
Current consumption system		[mA]	150	150	280	280
Operating temperature		[°C]		-15 to +40		
Dimensions (W x H x D)		[mm]	280 x 135 x 45	280 x 160 x 45	280 x 190 x 45	280 x 275 x 45
Weight		[kg]	0.628	0.750	0.871	1.168
					1.168	1.354