

Type		ASC 1708	ASC 1712	ASC 1716	ASC 1724	ASC 1732
Order No.		361017	361018	361019	361020	361021
EAN code		40 26187 280161	40 26187 280178	40 26187 280185	40 26187 280192	40 26187 280208
Inputs						
Satellite / IF				16		
Terrestrial				1		
Outputs						
Loop-through		17	17	17	17	17
Receiver		8	12	16	24	32
Further data						
Frequency range	SAT / IF	[MHz]		950 - 2150		
	Terrestrial			47 - 870		
Terrestrial amplifier		[dB]		23 - 25		
Gain	SAT / IF	[dB]	+3±1	+2±1	+2±1	+1±1
	Terrestrial		-1±1	-2±1	-3±1	-6±1
Equalizer	SAT	[dB]		+4±1		
Cascade loss	SAT / IF	[dB]	-2±1	-2±1	-3±1	-4±1
	Terrestrial		-5±1	-5±1	-5±1	-5±1
Max. signal input	SAT / IF	[dBμV]		98		
	Terrestrial			81		
Max. signal output	SAT / IF	[dBμV]		102		
	Terrestrial			85		
Return loss inputs / outputs		[dB]		10 / 14		
Isolation	SAT / SAT	[dB]		>33		
	SAT / Terr.			>37		
Current consumption receiver output		[mA]		41		
Current consumption system		[mA]	150	150	280	280
Operating temperature		[°C]		-15 to +40		
Dimensions (W x H x D)		[mm]	320 x 135 x 45	320 x 160 x 45	320 x 190 x 45	320 x 275 x 45
Weight		[kg]	0.753	0.835	1.032	1.314
					1.314	1.530