

GOING FUTURE TODAY.



Multiswitches with 4 SAT levels + terrestrial

innovative and reliable

easy and compact installation



ASC 5 series


- High insulated from each individual subscriber outputs
- High insulated SMPS power supply
- Able to work on low signals due to the high gain on subscriber outputs
- Easy and compact installation
- Low power usage due to new generation SMD components
- LNB supply 13 - 18 V
- suitable for Quad and Quattro LNBs
- LED subscriber control system
- 1 dB gain between first and last subscriber
- 13 - 18 V 22 kHz circuit




ASC 508



ASC 516



ASC 524



ASC 532

Technical data

Type	ASC 508	ASC 516	ASC 524	ASC 532
Order No.	361000	361001	361002	361003
EAN code	40 26187 271190	40 26187 271206	40 26187 280017	40 26187 280024
Inputs				
Satellite / IF			4	
Terrestrial			1	
Outputs				
Loop-through Receiver		5 8	5 16	5 24
Common data				
Frequency range SAT / IF Terrestrial	[MHz]		950 - 2150 47 - 870	
Terrestrial amplifier	[dB]		23 - 25	
Gain SAT / IF Terrestrial	[dB]	+3±1 -1±1	+3±1 -3±1	+3±1 -3±1
22 kHz generator			•	
Equalizer, SAT	[dB]		+4±1	
Cascade loss SAT / IF Terrestrial	[dB]	-2±1 -5±1	-3±1 -5±1	-3±1 -5±1
Max. signal input SAT / IF Terrestrial	[dBµV]		98 81	
Max. signal output SAT / IF Terrestrial	[dBµV]		102 85	
Return loss inputs / outputs	[dB]		10 / 14	
Isolation SAT / SAT SAT / Terr.	[dB]		>33 >37	
Current consumption receiver output	[mA]		48	
Current consumption system	[mA]	130	130	130
Operating temperature	[°C]		-15 to +40	
Dimensions (w x H x D)	[mm]	135 x 135 x 45	135 x 190 x 45	135 x 275 x 45
Weight	[kg]	0.345	0.465	0.625
				0.723