

Type		ASC 508	ASC 516	ASC 524	ASC 532
Order No.		361000	361001	361002	361003
EAN code		40 26187 271190	40 26187 271206	40 26187 280017	40 26187 280024
Inputs					
Satellite / IF				4	
Terrestrial				1	
Outputs					
Loop-through		5	5	5	5
Receiver		8	16	24	32
Further data					
Frequency range	SAT / IF	[MHz]	950 - 2150		
	Terrestrial		47 - 870		
Terrestrial amplifier		[dB]	23 - 25		
Gain	SAT / IF	[dB]	+3±1	+3±1	+3±1
	Terrestrial		-1±1	-3±1	-8±1
22 kHz generator			●		
Equalizer	SAT	[dB]	+4±1		
Cascade loss	SAT / IF	[dB]	-2±1	-3±1	-3±1
	Terrestrial		-5±1	-5±1	-5±1
Max. signal input	SAT / IF	[dBµV]	98		
	Terrestrial		81		
Max. signal output	SAT / IF	[dBµV]	102		
	Terrestrial		85		
Return loss inputs / outputs		[dB]	10 / 14		
Isolation	SAT / SAT	[dB]	>33		
	SAT / Terr.		>37		
Current consumption receiver output		[mA]	48		
Current consumption system		[mA]	130	130	130
Operating temperature		[°C]	-15 to +40		
Dimensions (w x H x D)		[mm]	135 x 135 x 45	135 x 190 x 45	135 x 275 x 45
Weight		[kg]	0.345	0.465	0.625
					0.723