

Type		ASC 908	ASC 912	ASC 916	ASC 924	ASC 932
Order No.		361005	361006	361007	361008	361009
EAN code		40 26187 280048	40 26187 280055	40 26187 280062	40 26187 280079	40 26187 280086
<b>Inputs</b>						
Satellite / IF				8		
Terrestrial				1		
<b>Outputs</b>						
Loop-through		9	9	9	9	9
Receiver		8	12	16	24	32
<b>Further data</b>						
Frequency range	SAT / IF	[MHz]		950 - 2150		
	Terrestrial			47 - 870		
Terrestrial amplifier		[dB]		23 - 25		
Gain	SAT / IF	[dB]	+3±1	+3±1	+3±1	+2±1
	Terrestrial		-1±1	-3±1	-3±1	-8±1
Equalizer	SAT	[dB]		+4±1		
Cascade loss	SAT / IF	[dB]	-2±1	-2±1	-3±1	-3±1
	Terrestrial		-5±1	-5±1	-5±1	-5±1
Max. signal input	SAT / IF	[dBμV]		98		
	Terrestrial			81		
Max. signal output	SAT / IF	[dBμV]		102		
	Terrestrial			85		
Return loss inputs / outputs		[dB]		10 / 14		
Isolation	SAT / SAT	[dB]		>33		
	SAT / Terr.			>37		
Current consumption receiver output		[mA]		48		
Current consumption system		[mA]	130	130	130	260
Operating temperature		[°C]		-15 to +40		
Dimensions (W x H x D)		[mm]	200 x 135 x 45	200 x 160 x 45	200 x 190 x 45	200 x 275 x 45
Weight		[kg]	0.520	0.645	0.770	1.120
					1.120	1.370