

Typ		CSA 9511 A	CSA 9511 A HF
Bestellnummer		750 952 (100 m, Ring) 750 955 (250 m, Abrollkartonage) 750 953 (500 m, Trommel)	750 956 (100 m, Ring) 750 958 (500 m, Trommel)
EAN-Code		4026187591892 (100 m, Ring) 4026187591908 (250 m, Abrollkartonage) 4026187591915 (500 m, Trommel)	4026187110680 (100 m) 4026187111168 (500 m, Trommel)
Innenleiter CU blank / massiv	[Ø mm]	1,13	1,13
Dielektrikum PEE gas-geschäumt	[Ø mm]	4,8	4,8
Mantel / PVC	[Ø mm]	6,9	6,9
minimaler Biegeradius	[mm]	35	35
Impedanz	[Ω]	75,0 ± 3,0	75,0 ± 3,0
Dämpfung @ 20°C			
55 MHz	[dB / 100 m]	4,2	4,2
230 MHz		8,0	8,0
300 MHz		9,8	9,8
500 MHz		12,1	12,1
860 MHz		17,0	17,0
1000 MHz		19,3	19,3
1800 MHz		26,3	26,3
2150 MHz		29,7	29,7
2400 MHz		-	-
Schirmungsmaß, Kopplungswiderstand			
		Klasse A+	
5 - 30 MHz	[dB]	< 2 mΩ / m	< 2 mΩ / m
30 - 1000 MHz		> 115	> 115
1000 - 2400 MHz		> 115	> 115
2400 - 3000 MHz		> 115	> 115