

License	Ord.nr.	Description	U 144-X	U 148-X	U 149-X	U 164-X	U 168-X
U SSL	380 133	To enable the SSL function activating the TLS protocol (SSL) for encrypted communication via https	<input checked="" type="checkbox"/>				
U Radius	380 136	For unlocking the RADIUS client-server-protocol	<input checked="" type="checkbox"/>				
U SPTS	380 146	To enable the SPTS streaming function	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	-	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
U 149 SPTS	380 153	U 149-X license to enable the SPTS streaming function	-	-	<input checked="" type="checkbox"/>	-	-
U Streamer MUX	380 147	For upgrading the Multiplex function in the frontend: EIT-calculation for the new output signals	1 x 4 in 4	2 x 4 in 4	-	1 x 4 in 4	2 x 4 in 4
U Carrier Monitoring	380 132	For unlocking the monitoring function; in case of deviating input signals from a reference value, the switch-off of the corresponding IP Tx is executed, ideal solution for IP-based satellite monitoring systems	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	-	-	-
U Blindscan	380 135	For unlocking the Blind Scan function; the streamer recognizes missing, additional and changed transponders after a reference scan of the spectrum: configurable scan range (frequency and symbol rate)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	-	-	-
U Streamer BISS	380 134	For unlocking the BISS function of U 100 streamer modules	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	-	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
U Wideband Mode	380 156	For unlocking wideband mode; reception of DVB-S2X transponders with max. data rate of 200 Mbit/s	-	-	<input checked="" type="checkbox"/>	-	-