

Typ		GUT MMD 7 SAT		
Bestellnummer		540 170		
EAN-Code		4026187120627		
		Multimedia-Stichdose mit SAT-Anschluss		

Anschlussdämpfung				
		5 - 65 MHz:	84 - 862 MHz:	950 - 2400 MHz:
Data	[dB]	7 ± 1		-
RF	[dB]	55	7,0 ± 1	-
TV	[dB]	55	7,0 ± 1	-
SAT	[dB]	55 typ.	30 typ.*	1,5 ± 1

Entkopplung				
	[MHz]	5 - 65 MHz:	470 - 862 MHz:	950 - 2400 MHz:
Data zu RF	[dB]	≥ 70	≥ 25	-
Data zu TV	[dB]	≥ 70	≥ 25	-
Data zu SAT	[dB]	≥ 70	≥ 25**	≥ 20***
TV zu RF	[dB]	-	≥ 20	-
TV zu SAT	[dB]	≥ 70	≥ 25**	≥ 20***
RF zu SAT	[dB]	≥ 70	≥ 25**	≥ 20***

Rückflussdämpfung				
		5 - 65 MHz:	84 - 862 MHz:	950 - 2400 MHz:
Data	[dB]	≥ 18 (-1,5 dB / Octave) F = 40 MHz		-
RF	[dB]	≥ 14 (-1,5 dB / Octave) F = 80 MHz		-
TV	[dB]	≥ 14 (-1,5 dB / Octave) F = 80 MHz		-
SAT	[dB]			> 10 (950 - 2400 MHz) linear abfallend bis 7,2 dB

* von 830 - 862 MHz 15 dB typ. ** von 830 - 862 MHz 20 dB typ. *** von 950 - 1050 MHz 15 dB typ.