

Type		X-A/V quad	X-A/V Multinorm twin	V 112
Order number		380 322	330 326	380 321
EAN-Code		4026187651589	4026187110864	4026187110857
Number of inputs		4	2	
<b>Audio / Video</b>				
Connectors		15-pole SUB-D-jack (2 A/V input signals per jack)*		
<b>Audio</b>				
Input level	[V RMS]	0,5		
Frequency range		40 Hz - 15 kHz		
Signal-to-noise ratio	[dB]	typ. 45		
<b>Video</b>				
Bandwidth		25 Hz - 4,8 MHz		
Input level	[V <sub>ss</sub> /75 Ω]	1		
<b>RF modulators</b>				
Connectors	[Ω]	IEC-Buchse, 75		
Output frequency range	[MHz]	47 - 862		
Output channels		K2 - K69		
Output level	[dBμV]	90 - 100		
Intermodulation distance	[dB]	typ. 60		
Reflection loss	[dB]	> 10		
Spurious frequency distance	[dB]	typ. 60		
TV standard		B, G (D/K on request)	PAL / SECAM B/G/D, Secam L, A2 / Nicam	
Video signal-to-noise ratio	[dB]	typ. 60		
channel selective output filter pluggable		-	-	<input checked="" type="checkbox"/>
<b>Common data</b>				
Power consumption	[W]	15	12	
Ambient temperature	[°C]	0...+50		0...+50

\* Adaptor cable VCP 15-2 for connection to source device required