

Type	V16.1	V16.13	V16.2	V16.23	V16.25	V16.3	V16.4
Order number	380 070	380 077	380 071	380 076	380078	380 080	380 090
EAN-Code 4026187...	...651282	...651787	...651299	...680114	...111076	...651220	...651237

Ausstattungs-Komponenten								
8 plug-in slots	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Bus-adapter	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
2 temperature controlled fans	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Power supply VSN 1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	-	-	-	<input checked="" type="checkbox"/>	-	
Power supply VSN 2 (redundant)	-	-	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	-	<input checked="" type="checkbox"/>	
prepared for 16 AV- or 32 D-Sub-inputs	-	<input checked="" type="checkbox"/>	-	-	<input checked="" type="checkbox"/>	-	-	
SAT distribution field VMS 616	-	-	-	-	-	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	
prepared for BNC-jacks (for ASI modules)	-	-	-	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	-	-	
seperate outputs	-	-	-	-	<input checked="" type="checkbox"/>	-	-	

Common data		
Supply voltage	[V-/Hz]	230 / 50
EMC		according EN 50083 T2 / A1
Ambient temperature	[°C]	0...+50
Dimensions (W xH x D) with mounting brackets frontside with mounting brackets backside	[mm]	340 x 426 x 277 (19" / 7 HU base unit) 340 x 491 x 277 340 x 491 x 290 + 3 HU for air flow metal plate VAF
Weight	[kg]	9,6
Power consumption	[W]	maximum 200